Tersus TC40 Controller



Overview

The Tersus TC40 Controller is a rugged smart phone with design of 8" IPS screen and 1280*800 resolution. Equipped with Android 8.1 mainstream operating system, 8-core 2.0G processor, it is perfect to adapt with Tersus Survey software and run fastly. The 9000mAh large capacity battery is detachable, which can work continuously for 10 hours without pressure. The unique rounded corner design and plastic shell are compatible with appearance and protection. With professional IP67 rating, it is robust and reliable for harsh operating conditions.

Key Features

8" IPS screen, 1280*800 resolution

Android 8.1 operating system

8-Core 2.0GHz CPU

4GB RAM + 64GB ROM

Front 5 megapixels fixed focus, Rear 13 megapixels auto focus camera

IP67 certified grade, water/shock/dust proof

9000mAh battery

Wi-Fi, Bluetooth, NFC

Supports GPS,BDS & GLONASS

Unique rounded corner design & plastic shell





Technical Specifications

System

Cyclom	
Operating System:	Android 8.1
CPU:	8-Core 2.0GHz
Memory:	4GB RAM + 64GB ROM
Camera:	Rear 13 Megapixels AutoFocus; High-Brightness LED Flash; Front 5 Megapixels Fixed Focus
Display:	8" IPS Screen
Resolution:	1280x800
Touch Screen:	5-point Capacitive Touch Screen
Moudle; 6 pin	Extended Port, used for Fingerprint Pogo Port ,used to connect Charger
External Storage:	Micro SD*1, Up to 128GB
Keypad :	6 Physical Buttons, 1 Power Button
Earphone:	3.5mm Earphone Jack
Audio: Volu	Rear Stereo Speakers, me $90 ext{db}\pm3 ext{db}$ (Test Distance $10 ext{cm}$)
Notification Metho	od: Sound, Vibrtation, LED Prompt
Fingerprint Moudl	e: TCS1G Reserved
EAN13, EAN8, UPC Codabar, UCC/EAN ISBN, Standard 25,	Support Code System: CA, UPCE, Code 128, Code 39, N128,RSS, ITF, ITF14, ITF6 , IS SN, AZTEC,Matrix 25,Industrial 25, ey, Code 11, Code 93,PDF417, QR

Code, DataMatrix, Hanxin code, Maxicode, Micro

GPS, BDS, GLONASS

QR, Micro PDF417, Composite

GNSS

Signal Tracking:

Communication

Cellular Mode:	Dual SIM Dual Standby
SIM1 & SIM2:	
	FDD-LTE B1/B3/B5/B7/B8
	TDD-LTE B38/B39/B40/B41
	TDSCDMA B34/B39
	WCDMA B1/B2/B5/B8
	GSM B2/B3/B5/B8
	CDMA1 _x /CDMA2000 BC0/BC1
Bluetooth:	RT4 1 & RIF

Wi-Fi: IEEE 802.11a/b/g/n 2.4G 5G Double Frequency

Diuetoutii.	D14.1 & DLC

RFID(High Frequency)

Support Agreement: ISO14443A/B, ISO15693 NFC Reading Distance: $0^{\sim}5cm$

Sensors: Gravity Acceleration Sensor Geomagnetic Sensor, Light and Distance Sensor

Electrical

Battery:		9000mAh
Working Time(Typical):		≥10 Hours
Charging Ways:	USB TYPE-C Fast	Charge 5V/9V 1.5A

Physical

Dimension:		235mmx150mmx17.6mm	
Weight:		700g (Include Battery)	
Operating Temperature:		-20 °C ~ +55 °C	
Storage Temperature:		-30 °C ~ +70 °C	
Operating Humidity:		5% ~ 95%	
Dustproof & Waterproof:		IP67	
Shock:	1.2m Drop Onto Concrete(6 Sides		
Electrostatic Protection:		±15kV Air Discharge; ±8kV Contact Discharge	

Website | www.tersus-gnss.com
Sales Inquiry | sales@tersus-gnss.com
Technical Support | support@tersus-gnss.com

